

## HIGHTEC BRAKE FLUID SUPER DOT 5.1

Fully synthetic, low viscosity brake fluid with improved dry and wet boiling behaviour in compliance with DOT 5.1 and ISO Class 5.1.

### Description

HIGHTEC BRAKE FLUID SUPER DOT 5.1 is a fully synthetic, low viscosity brake fluid with improved dry and wet boiling behaviour based on glycols with oxidation and corrosion inhibitors.

### Application

HIGHTEC BRAKE FLUID SUPER DOT 5.1 is used in hydraulic brake and clutch systems in accordance with the manufacturer's specifications. It is miscible and compatible with commercially available brake fluids according to DOT 3, DOT 4 and DOT 5.1.

### The quality of this product is equivalent to EU regulations

- FMVSS 116 DOT 3/DOT 4/DOT 5.1
- SAE J 1703/1704
- ISO 4925 Class 3/4/5.1
- JIS K2233 Class 3/4/5

### Benefits

- Multi-functional use in passenger cars, commercial vehicles, buses, as well as agricultural and construction machinery if a brake fluid is required according to one of the above mentioned specifications
- The low viscosity and very good viscosity-temperature behaviour ensure rapid controlled braking operations by the ABS and ESP systems
- The very high dry and wet boiling points provide additional protection against vapour lock when severe stress is imposed on the brake system.
- It is backward compatible with conventional DOT 3 and DOT 4 brake fluids
- Protection of brake and clutch hydraulics against deposits and corrosion
- Miscible and compatible with other synthetic brake fluids. However, in order to exploit the full product benefits, a complete brake fluid change is recommended.

### Notices

Under no circumstances may HIGHTEC BRAKE FLUID SUPER DOT 5.1 be mixed with mineral or silicone-based fluids (e.g. LHM or DOT 5).

### Typical characteristics

| Property                     | Method                      | Unit               | Value          |
|------------------------------|-----------------------------|--------------------|----------------|
| Density at 20 °C             | ASTM D1122                  | g/ml               | 1,065          |
| Flash point                  | ASTM D-92 / DIN EN ISO 2592 | °C                 | > 120          |
| Viscosity at -40 °C          | DIN EN ISO 3104             | mm <sup>2</sup> /s | 900            |
| Boiling point ERBP           | FMVSS 116                   | °C                 | 270 (min. 260) |
| Wet boiling point Wet - ERBP | FMVSS 116 SAE J1703/1704    | °C                 | 183 (min. 180) |

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe.com.de).

Are you looking for the correct oil for your vehicle?  
Scan this code for the ROWE-oilfinder.



25104 | 14.03.2017