Telefax: +49 (0)6241 5906-999



Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC DIESEL FLOW FIT

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: ROWE MINERALOELWERK GMBH

 Street:
 Langgewann 101

 Place:
 D-67547 Worms

 Telephone:
 +49 (0)6241 5906-0

e-mail: info@rowe-mineraloel.com
Internet: www.rowe-mineraloel.com

Responsible Department: SDB@rowe.com.de

1.4. Emergency telephone Giftnotruf Mainz (DE; E) +49 (0)6131-19240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aspiration hazard: Asp. Tox. 1 Carcinogenicity: Carc. 2

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May be fatal if swallowed and enters airways.

Suspected of causing cancer.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons C11-C14 N-Alkanes , Isoalkans, Cyclics Aromatics (2-25%)

HYDROCARBONS, C14-C18, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-30%)

naphthalene

Signal word: Danger

Pictograms:



Hazard statements

H351 Suspected of causing cancer.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P281 Use personal protective equipment as required.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.



according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 2 of 9

P501

Dispose of contents/container to of the disposal according to local regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	GHS Classification	•				
1174522-15-6	Hydrocarbons C11-C14 N-Alkanes , Isoalkans, Cyclics Aromatics (2-25%)					
	925-653-7		01-2119458869-15			
	Asp. Tox. 1, Aquatic Chronic 3; H30	04 H412				
1174522-18-9	HYDROCARBONS, C14-C18, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-30%)					
	920-360-0		05-2114132820-60			
	Asp. Tox. 1; H304					
95-63-6	1,2,4-trimethylbenzene					
	202-436-9	601-043-00-3	01-2119472135-42			
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Aquatic Chronic 2; H226 H332 H315 H319 H335 H411					
91-20-3	naphthalene					
	202-049-5	601-052-00-2	01-2119561346-37			
	Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H351 H302 H400 H410					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After contact with skin

Wash with plenty of water. Immediately remove any contaminated clothing, shoes or stockings. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Induce vomiting when the affected person is not unconscious. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.



according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 3 of 9

5.2. Special hazards arising from the substance or mixture

Non-flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
91-20-3	Naphthalene	10	50		TWA (8 h)	EU
95-63-6	Trimethylbenzenes: 1,2,4-Trimethylbenzene	25	125		TWA (8 h)	WEL

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 4 of 9



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: whitish
Odour: characteristic

pH-Value: not determined

Changes in the physical state

Melting point: $-19 \, ^{\circ}\mathrm{C}$ Initial boiling point and boiling range: $156\text{-}280 \, ^{\circ}\mathrm{C}$ Flash point: $65 \, ^{\circ}\mathrm{C}$

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 0,6 vol. %
Upper explosion limits: 7 vol. %
Ignition temperature: 240 °C

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Print date: 03.02.2020



Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 5 of 9

Density (at 15 °C): 0,83 g/cm³

Solubility in other solvents

not determined

Partition coefficient: VOC g/l 783,8
Viscosity / kinematic: 7,8 mm²/s

(at 40 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects



according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 6 of 9

Acute toxicity

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
1174522-15- 6	Hydrocarbons C11-C14 N-Alkanes , Isoalkans, Cyclics Aromatics (2-25%)							
	oral	LD50 mg/kg	5050	Rat				
	dermal	LD50 mg/kg	3400	Rabbit				
	inhalation (4 h) vapour	LC50 mg/l	>13,1	Rat				
1174522-18- 9	HYDROCARBONS, C14	-C18, N-ALK	KANES, ISO	ALKANES, CYCLICS,AR	OMATICS (2-30%)			
	oral	LD50 mg/kg	>4150	Rat				
	dermal	LD50 mg/kg	1700	Rabbit				
	inhalation (4 h) vapour	LC50 mg/l	>5,28	Rat				
95-63-6	1,2,4-trimethylbenzene							
	oral	LD50 mg/kg	5000	Rat	RTECS			
	inhalation (4 h) vapour	LC50	18 mg/l	Rat	RTECS			
	inhalation aerosol	ATE	1,5 mg/l					
91-20-3	naphthalene							
	oral	ATE mg/kg	500					

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 7 of 9

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
1174522-15- 6	Hydrocarbons C11-C14 N-Alkanes , Isoalkans, Cyclics Aromatics (2-25%)						
	Acute fish toxicity	LC50	9,2 mg/l	96 h			
	Acute algae toxicity	ErC50	2,9 mg/l		Pseudokirchneriella subcapitata Pseudokirchneriella subcapitata		
1174522-18- 9	HYDROCARBONS, C14-C18, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-30%)						
	Acute fish toxicity	LC50 mg/l	10-30		Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 mg/l	4,6-10	72 h	Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 mg/l	10-22	48 h	Daphnia magna	OECD 202	
95-63-6	1,2,4-trimethylbenzene						
	Acute fish toxicity	LC50 mg/l	7,72	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50	3,6 mg/l	48 h	Daphnia	ECOTOX	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1174522-18-9	HYDROCARBONS, C14-C18, N-ALKANES, ISOALKANES, CYCLICS,AROMATICS (2-30%)	>3,5
95-63-6	1,2,4-trimethylbenzene	3,63

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130703 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); wastes of liquid fuels; other fuels (including mixtures); hazardous

waste

List of Wastes Code - used product

Print date: 03.02.2020



Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 8 of 9

130703 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); wastes of liquid fuels; other fuels (including mixtures); hazardous

waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: 1,2,4-trimethylbenzene

2004/42/EC (VOC): 783,8 g/l

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):



according to Regulation (EC) No 1907/2006

HIGHTEC DIESEL FLOW FIT

Revision date: 10.07.2019 Page 9 of 9

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,9,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)